

PAPERMINT

TECHNICAL SHEET

Uptade 09/10/2018

VELVET

SUPPORT - TECHNICAL DATA

HESSIAN - X - X - X

CONSTRUCTION			
	Chaine/ Warp	Trame/ Weft	
Nb thread/ cm	X	X	
Metric thread (Nm)	X	X	
Average yarn number	X		
Tear (N)		X	
Rupture (N/cm)	X	X	
	Cycles	Abrasion	Pilling
Martindale	X	X	X

MANUFACTURE

Support: **VELVET**

Process: **INR:AS**

1. 21. Impression numérique/ Imp°num. ReNOIR 150 cm
2. 60. SIL Softener Finish.

MAINTENANCE

Machine wash 40°C

No chlorine or bleach

Drying machine average temperature

Ironing max. 150°C

No dry cleaning

TESTS ET STANDARDS

Light fastness: 4/5 - Norme ISO 105 B02

Abrasion Martindale: Norme ISO 12947

Rupture, tensile strength: Norme ISO 13935

Tear primed: Norme ISO 13937

• **Le showroom PaperMint** •

36, Rue Pierre Sépard 75009 Paris · France ·

+33 9 87 01 56 95

commande@paper-mint.fr – paper-mint.fr

Instagram : @papermint_paris – Facebook : /papermintparis